

QLSR.MH8007 - Pipe Joint Sealing Compounds

Pipe Joint Sealing Compounds

[See General Information for Pipe Joint Sealing Compounds](#)

HENKEL CORP

MH8007

ONE HENKEL WAY
ROCKY HILL, CT 06067 USA

Loctite 5030 Dri Seal For use in devices handling propane, butane and natural gas (pressure not over 100 psig) not exceeding 2 in. pipe size.

Loctite Sprinkler System Thread Sealant For use in devices handling gasoline, petroleum oils, natural gas (pressure not over 300 psig) and butane not exceeding 2 in. pipe size.

Loctite® Threadlocker® 271 For use in devices handling gasoline, petroleum oils, natural gas (pressure not over 300 psig), butane and propane not exceeding 2 in. pipe size.

Loctite® Gasket Eliminator® 515 For use in devices handling gasoline, petroleum oils, natural gas (pressure not over 300 psig), butane and propane not exceeding 2 in. pipe size.

Loctite® PST® 561 Pipe Sealant For use in devices handling gasoline, petroleum oils, natural gas (pressure not over 300 psig), propane and butane not exceeding 2 in. pipe size.

Loctite® PST® 565 Pipe Sealant For use in devices handling gasoline, petroleum oils, natural gas (pressure not over 300 psig) and butane not exceeding 2 in. pipe size.

Loctite® PST® 567 with PTFE For use in devices handling gasoline and petroleum oils, natural gas (pressure not over 300 psig), propane, butane, not exceeding 2 in. pipe size.

Last Updated on 2020-08-11

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certification Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners.

[Learn More](#)

[Cookie Settings](#)

Accept