

QMFZ2.E182771 - Plastics - Component

Plastics - Component

[See General Information for Plastics - Component](#)

HENKEL AG & CO KGAA
 Henkelstrasse 67
 40589 Dusseldorf, GERMANY

E182771

Material Dsg	Color	Min. Thk mm	Flame Class	H H		Elec	RTI		H D		
				W	A		Mech	Imp	Str	V	4
				I	I				R	5	T
Polyamide (PA), Hot Melt Adhesive, "Technomelt PA", furnished as granular material.											
113	NC	0.67	V-0	-	-	65	65	65	-	-	-
		0.75	V-0	-	0	65	65	65			
		1.0	V-0	4	0	65	65	65			
652, 7852	NC	1.1-1.3	V-0	-	-	65	65	65	-	-	-
657 black, 7857 black											
	BK	1.1-1.3	V-0	-	-	65	65	65	-	-	-
673, 7873 black	AM	1.2-1.4	V-0	-	-	65	65	65	-	-	-
678 black, 7878 black											
	BK	1.6-1.8	V-0	5	0	65	65	65	-	-	-
Polyamide (PA), "Technomelt PA", furnished as granular material.											
2035	NC	1.8-2.1	V-0	-	-	65	65	65	-	-	-
6208 N	NC	1.0-1.5	V-2	-	-	65	65	65	-	-	-
6208 N black (f2)	BK	1.0	V-0	-	-	95	65	95	-	-	0
		1.2	V-0	3	0	95	65	95			
		3.0	V-0	2	0	95	65	95			
6211	NC	1.1-1.8	V-0	-	-	65	65	65	-	-	-
633 N	NC	1.0-3.0	V-2	-	-	65	65	65	-	-	-
638 black, 7838 black											
	BK	1.0	V-0	-	-	65	65	65	-	-	-
646 black, 7846 black											

	BK	1.0-1.1	V-0	5	0	65	65	65	-	-	-
6481 black (f2)	BK	1.0	V-2	4	2	65	65	65	-	-	0
		1.2	V-2	4	2	65	65	65			
		2.0	V-2	4	2	65	65	65			
		3.0	V-2	3	2	65	65	65			
651	GY	1.0	V-0	4	0	65	65	65	-	-	0
		3.0	V-0	3	0	65	65	65			
668 white	WT	1.0	V-0	4	0	65	65	65	-	-	0
		3.0	V-0	3	0	65	65	65			
676 black	BK	1.0	V-2	3	0	65	65	65	-	-	0
		3.0	V-2	3	0	65	65	65			
6790	NC	1.0-1.8	V-0	-	-	65	65	65	-	-	-
6790 black	BK	1.0-1.3	V-0	-	-	65	65	65	-	-	-
6797	NC	1.0-2.0	V-0	-	-	65	65	65	-	-	-
6830 black	BK	.95 - 1.1	V-0	-	-	65	65	65	-	-	-
6832 black	BK	.97 - 1.2	V-0	-	-	65	65	65	-	-	-
6839 black	BK	1.0	V-0	-	-	65	65	65	-	-	-
		3.0	V-0	-	-	65	65	65			
Polyamide (PA), "Technomelt PA", furnished as pellets.											
PA 2692 N	AM	3.0-3.2	V-2	-	-	65	65	65	-	-	-
PA 668 N	NC	3.0-3.2	V-2	-	-	65	65	65	-	-	-
Polyolefin, "Technomelt", furnished as granular material.											
AS 5376	NC	1.0	V-2	-	-	50	50	50	-	-	-
		3.0	V-2	-	-	50	50	50			
Polyurethane (PUR), "Loctite", furnished as two liquid components.											
Loctite CR 6127 (a)/ Loctite CR 4300 (b)											
	NC	9.0	V-0	-	-	50	50	50	-	-	-
Loctite CR 6127 SB15(a) / Loctite CR 4300											
	BK	9.0	V-0	-	-	50	50	50	-	-	-
Silicone Rubber (SIR), "Loctite SI", furnished as two components (paste).											
5610	BK	1.5	HB	3	1	105	105	105	-	-	0
		3.0	HB	2	1	105	105	105			

5615	BK	1.5	HB	3	1	105	105	105	-	-	0
		3.0	HB	2	1	105	105	105			

(a) - May be followed by a suffix to indicate all pot life.

(b) - natural color looks white

(f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL.

Marking: Company name and material designation on container, wrapper or finished part.

Last Updated on 2020-10-23

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"